


# K-12


直進タイプ スプレーノズル



BSBM				
管径 in	寸法 mm			重量 g
	A	B	C	
¼	35	11	13	32

SUS				
管径 in	寸法 mm			重量 g
	A	B	C	
¼	36	11	14	32



管径 in	寸法 mm		重量 g
	A	B	
¼	20	10	15
⅜	24	11	30
½	32	14	63
¾	39	17	115
1	52	22	240

ストレーナ付

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度													
		水圧 (MPa)	0.0196	0.029	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490	0.686	0.980
		(kg/cm <sup>2</sup> )	0.2	0.3	0.5	0.7	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
¼	0.5								0.190	0.210	0.230/55°	0.265/55°	0.300/55°	0.355/60°	0.410/60°
	0.7								0.410	0.450	0.490/70°	0.540/70°	0.680/75°	0.710/75°	0.810/75°
	1.0								0.655	0.725	0.800/70°	0.895/75°	0.990/75°	1.170/70°	1.380/60°
	1.2								0.900	1.000	1.090/75°	1.270/75°	1.360/70°	1.540/65°	1.820/60°
	1.6								1.160	1.320	1.460/60°	1.690/60°	1.900/60°	2.240/60°	2.640/55°

ストレーナ無

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度														
		水圧 (MPa)	0.0196	0.029	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490	0.686	0.980	
		(kg/cm <sup>2</sup> )	0.2	0.3	0.5	0.7	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	
¼	2.0	-	-	1.60/40°	1.90/45°	2.45/50°	3.20/55°	3.60/55°	3.90/55°	4.20/55°	4.63/50°	5.00/50°	6.00/50°	6.50/45°		
	2.4			1.60/40°	2.00/45°	2.40/50°	2.90/55°	3.60/55°	4.30/60°	4.90/60°	5.40/60°	6.20/55°	6.90/50°	8.20/50°	9.40/45°	
	2.6			1.80/45°	2.20/40°	2.70/55°	3.10/55°	3.65/60°	4.45/60°	5.20/60°	5.90/60°	6.50/60°	7.50/60°	8.40/50°	10.05/50°	11.40/50°
	3.2			2.60/45°	3.00/50°	3.80/55°	4.40/55°	5.20/60°	6.40/60°	7.40/60°	8.20/60°	8.80/60°	10.00/60°	11.00/50°	13.20/50°	14.80/50°
⅜	2.8			2.10/40°	2.70/40°	3.30/45°	3.80/45°	4.50/50°	5.40/50°	6.20/50°	6.80/50°	7.40/50°	8.40/45°	9.25/45°	11.00/45°	12.40/40°
	3.2			3.40/40°	4.00/40°	4.80/50°	5.30/50°	6.20/55°	7.30/55°	8.40/55°	9.30/55°	10.00/55°	11.20/50°	12.30/50°	14.60/46°	16.60/45°
	3.6			4.00/40°	4.60/45°	5.50/50°	6.30/55°	7.60/60°	9.20/60°	10.60/60°	11.80/60°	12.65/60°	14.00/55°	15.30/53°	18.20/50°	21.00/47°
	4.0			4.90/40°	6.00/50°	7.45/55°	8.40/60°	9.80/60°	12.00/65°	13.60/70°	14.60/70°	15.40/70°	17.30/65°	18.80/60°	22.00/55°	24.80/50°
	4.8			6.10/40°	7.30/45°	8.90/60°	10.50/65°	12.90/70°	15.20/80°	17.05/85°	18.50/85°	19.60/85°	21.20/80°	23.00/80°	26.60/70°	29.60/70°
½	4.8			7.00/40°	8.20/40°	10.50/45°	12.30/50°	14.40/60°	17.20/65°	19.20/65°	20.80/65°	22.40/65°	25.40/60°	28.00/55°	33.00/50°	37.00/50°
	5.5			7.90/40°	9.10/40°	11.50/45°	13.40/50°	16.30/60°	19.50/65°	21.80/65°	24.00/65°	26.20/65°	29.40/60°	32.40/55°	38.50/50°	44.00/50°
	6.0			8.80/45°	10.20/50°	12.90/60°	15.00/60°	17.90/65°	21.80/70°	24.60/75°	27.00/75°	28.70/75°	32.30/70°	35.90/65°	43.60/60°	50.10/60°
	6.4			9.40/50°	11.40/50°	13.60/60°	15.40/65°	18.50/70°	22.60/80°	25.20/85°	28.30/85°	30.10/85°	34.80/80°	38.40/75°	46.40/70°	53.00/70°
¾	6.4			10.00/60°	13.20/60°	16.40/60°	19.20/60°	22.90/65°	27.00/70°	30.30/70°	32.50/70°	35.80/70°	40.00/65°	43.80/65°	53.00/60°	60.00/60°
	7.5			12.00/60°	16.60/60°	21.50/60°	24.40/65°	28.20/70°	35.20/75°	40.30/75°	43.80/75°	47.00/75°	53.00/70°	58.40/70°	70.00/65°	80.00/60°
	9.0			17.00/60°	22.00/60°	26.00/65°	30.00/70°	36.00/75°	45.00/80°	49.80/85°	54.40/85°	58.80/85°	67.50/80°	74.50/75°	89.00/70°	100.00/70°
1	8			18.00/60°	22.00/60°	27.00/60°	31.50/65°	37.50/70°	44.50/80°	49.50/80°	54.50/85°	59.00/85°	67.00/80°	73.50/70°	88.50/70°	99.00/70°
	10			-	-	36.00/60°	43.00/65°	50.50/70°	60.50/80°	69.00/80°	76.00/85°	83.50/85°	96.00/80°	105.00/70°	121.00/70°	140.00/70°
	12			-	-	44.00/60°	57.00/65°	67.00/70°	80.00/80°	92.00/80°	102.50/85°	112.00/85°	128.00/80°	143.00/70°	167.50/70°	200.00/70°

※記載の数値は代表値であり、保証値ではありません。