


# K-22

直進タイプ スプレーノズル



管径 in	寸法 mm		重量 g
	A	B	
3/8	31	19	36

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度										
		水圧 (MPa) (kg/cm <sup>2</sup> )	0.029	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490
3/8	2.0		0.90/65°	1.01/70°	1.23/75°	1.42/75°	1.72/80°	2.05/80°	2.25/80°	2.45/80°	2.75/80°	3.00/80°
	2.5		1.01/65°	1.16/70°	1.35/75°	1.65/75°	2.02/80°	2.35/80°	2.65/80°	2.80/80°	3.15/80°	3.45/80°
	3.0		1.40/60°	1.80/70°	2.15/75°	2.70/75°	3.20/75°	3.65/80°	4.10/80°	4.40/80°	4.90/80°	5.25/80°
	3.5		1.65/60°	2.06/70°	2.40/75°	3.05/75°	3.70/80°	4.26/80°	4.70/80°	5.01/80°	5.50/80°	6.00/80°
	4.0		1.81/65°	2.20/75°	2.65/80°	3.36/80°	4.00/80°	4.52/85°	5.15/85°	5.67/85°	6.60/80°	7.90/80°

※記載の数値は代表値であり、保証値ではありません。