


K-20

直進タイプ スプレーノズル



管径 in	寸法 mm			重量 g
	A	B	C	
¼	29	10	8	100

管径 in	吹出穴 mm	水 量 L/min / Spray 角 度											
		水圧 (MPa) (kg/cm ²)	0.049	0.069	0.098	0.147	0.196	0.245	0.294	0.392	0.490	0.686	0.980
¼	1.2			0.34/40°	0.39/45°	0.46/55°	0.54/60°	0.62/60°	0.68/60°	0.76/65°	0.84/70°	1.08/80°	1.20/70°
	1.6			0.55/45°	0.65/45°	0.79/55°	0.90/60°	0.98/60°	1.10/60°	1.24/65°	1.39/70°	1.75/80°	2.00/70°
	2.0			0.86/45°	1.02/45°	1.22/60°	1.43/60°	1.57/65°	1.73/65°	1.93/70°	2.24/75°	2.69/80°	3.10/70°
	2.4			1.10/50°	1.40/60°	1.80/60°	2.15/70°	2.50/80°	2.65/75°	3.00/80°	3.20/80°	3.60/80°	4.20/70°
	2.8			1.60/50°	2.05/60°	2.45/70°	2.75/80°	3.05/80°	3.30/80°	3.65/80°	4.00/80°	4.65/70°	5.45/70°
	3.2			1.90/60°	2.40/70°	2.90/80°	3.40/80°	3.80/80°	4.20/80°	5.00/80°	5.70/70°	6.75/70°	8.00/70°

※記載の数値は代表値であり、保証値ではありません。